The Arab American University Purchasing Procurement Dep.



الجامحة العربية الإمريكية دائرة اللوازم والمشتريات

التاريخ: 19/12/2023		رقم الاستدراج:	Q046.2024
السادة:			
تلفون:أجهزة ط	أجهزة طبية		
إيميل:			

BR2224-000103-017-006

استدراج عروض أسعار: الرجاء تزويدنا بأسعار اللوازم التالية شامل لضرببة القيمة المضافة:

اجمالي تكلفة البند	السعر	الكمية	الوحدة	اسم الصنف	
		1	عدد	Vital Sign monitor المواصفات صفحة 2.3	1
		1	عدد	Horizontal Gel electrophoresis systems. المواصفات صفحة 4.3	2
		1	عدد	Benchtop PH meter المواصفات صفحة 6.5	3
		3	326	Thermal Sealing Machine for Autoclave Bags المواصفات صفحة 7.6	4
	دولار	رش.ض)	المجموع الكلم		

ختم وتوقيع المورد:	تعليمات الاستدراج		
	الثلاثاء	آخر موعد لتسليم العروض هو يوم:	**
	26/12/2023	الموافق:	**
	أجهزة طبية	طبيعة البنود المطلوبة:	**
	دولار	بعملة:	**
	الحرم الرئيسي - جنين	الأسعار تشمل التوصيل ل:	**
	تورید کامل	نوع التوريد:	**
	بالظرف المغلق	يرجى إرسال العرض ب:	**

شروط الاستدراج:

- ** ضرورة تحديد مدة الكفالة إن وجدت.
- ** ضرورة تحديد مدة التوريد من تاريخ استلام امر الشراء، و في حال عدم الالتزام يتم فرض غرامة تأخير .
- ** ختم وتوقيع المورد المعتمد على هذا النموذج، وكتابة رقم الاستدراج واسم الشركة كما هو مسجل لدى الضريبة على الظرف.
 - ** للمراجعة والاستفسار بخصوص المواصفات يرجى الاتصال على هاتف 042418888 رقم داخلي 1481
- ** للمراجعة والاستفسار بخصوص المواصفات عن طريق فاكس 042510972 أو بريد الكتروني manal.daraghmah@aaup.edu
 - ** لمشاهدة العطاءات والاستدراجات، يرجى الدخول الى الرابط http://www.aaup.edu/tenders



Vital Sign monitor

Origin: USA Europe japan

Brand name

• Lightweight and portable.

Display: 85 x 100 mm

For adult & pediatric

With memory.

Display & Measurement :

NIBP: DIA adult (21 to 220 mmHg), pediatric (21 to 120 mmHg), Neonate (21 to 100 mmHg)

NIBP: SYS adualt (41 to 255 mmHg), pediatric (41 to 160 mmHg), Neonate (41 to 130 mmHg)

Pulse range: 25 to 220 BPM WITH ACCURACY ± 2%

• Spo2:

Range: 0 to 100%

Saturation Accuracy: 70 to 100 % ± 2%

• Temperature:

Measurement range 0 to 100 %

Accuracy at 33 C \pm 0.2 Display resolution : 0.1 C .

Power source :

Direct

Internal battery 12V 2100 mAh

Operation time 4 hours.

price include all accessories (sensors , probe , cuff , ..) to work completely for above parameter

Optional price:

Internal printer with paper Mobile stand with counter weight Reusable spo2 sensor

يجب تعبئة الجدول بالأسفل بالإضافة الى تقديم عرض الشركة التقني

comments) Manufacture Model
Madel
14100101
Origin
Delivery time
Yes / No



display & Measurement :	Yes / No
NIBP: DIA adult (21 to 220 mmHg) , pediatric (21 to 120 mmHg) , Neonate (21 to 100 mmHg)	Yes / No
NIBP: SYS adult (41 to 255 mmHg), pediatric (41 to 160 mmHg), Neonate (41 to 130 mmHg)	Yes / No
NIBP: MAP adult (26 to 210 mmHg) , pediatric (26 to 133 mmHg) , Neonate (26 to 120 mmHg)	Yes / No
Pulse range: 25 to 220 BPM WITH ACCURACY ± 2%	Yes / No
Spo2: Range: 0 to 100%, Saturation Accuracy: 70 to 100 % ± 2%	Yes / No
Temperature :	Yes / No
Measurement range 0 to 100 %	Yes / No
Accuracy at 33 C ± 0.2	Yes / No
Display resolution: 0.1 C.	Yes / No
Power source :	Yes / No
Direct	Yes / No
Internal battery 12V 2100 mAh	Yes / No
Price include all accessories (sensors, probe, cuff,) to work completely for above parameter	Yes / No
Mobile stand with counter weight	Yes / No
Reusable spo2 sensor	Yes / No
Your warranty must be include all spare parts and labor .	Yes/Na
Price should be include installation and team training in site .	Yes / No
Service & operation manuals are included & Date of manufacturing of system not less than 2022.	Yes / No

Horizontal Gel electrophoresis systems.

Complete set including:

systems make the whole process of running DNA gels, viewing DNA bands and documenting results easy. All without removing the gel.

large and small electrophoresis gel tank , blue led light , UV transparent tray, safety lid, casting trays with stand and combs , with integrated power supply for system and led illumination

, with glasses

Power supply:

Power Supply suitable for above horizontal gel electrophoresis

Power supply: 30up to - 100 V

Programmable methods.

Timer control .

Pause and resume function.

Safety: no load detection, sudden load change detection, overload/short circuit detection and over voltage protection.

Complete system and ready to use.

Kindly your offer will not be taken into our consideration if you don't fill below table.



Horizontal Gel Electrophoresis	Yes/No	Comment
Manufacture for power supply and tank	Manufacture	
Origin: USA, Europe , japan	Origin	
Delivery time	Delivery time	
3years Full warranty	Yes/No	
Complete set including :	Yes/No	*
	Yes/No	
systems make the whole process of running DNA gels, viewing DNA bands and documenting results easy. All without removing the gel.		
large and small electrophoresis gel tank , blue led light , UV transparent tray, safety lid, casting trays with stand and combs , with integrated power supply for system and led illumination	Yes/No	
, with glasses	Yes/No	
Power supply:	Yes/No	**************************************
Power Supply suitable for above horizontal gel electrophoresis	Yes/No	
Power supply: 30up to - 100 V	Yes/No	
Programmable methods.	Yes/No	
Timer control .	Yas/No	
Pause and resume function.	Yes/No	
Safety: no load detection, sudden load change detection, overload/short circuit detection and over voltage protection.	Yes/No	
Complete system and ready to use.	Yes/No	
	Yes/No	
10 years availability for spare parts	Yes/No	
Complete and Ready to use with all accessories	Yes/No	
User's and service manual	Yes/No	
Price include installation and training in site	Yes/No	
Date of manufacture not less than 2022	Yes/No	



Benchtop PH meter.

Brand name, USA, Europe origin

- Applications : general laboratory use .
- Parameter: PH.mV, Temp,
- Bench top .
- PH range: -1 − 14 .
- Temperature range: -5 105 °C.
- PH and temperature probe (plastic not glass).
- Accuracy: 2%.
- Temperature: manual by key or automatic recognized by probe (ATC).
- Easy to read on a large screen .
- calibration: automatic one or two point for buffer (4,7,10).
- memory :memory data and calibration memory .
- Include startup set buffer Solution . (4,7,14).
- Stand for probes.
- Dust cover .
- Water proof .
- Complete system and ready to use with all necessary solution for (calibration, cleaning, storage) and probe stand.

Optional Accessories (quote it separately):

PH probe

Kindly your offer will not be taken into our consideration if you don't fill below table.

Bench top PH meter	Yes/No	Comment
anufacture	Manufacture	
odel	Model	
igin	' Origin	
livery time	Delivery time	100 CO 10
years warranty and 10 years availability for spare parts	Yes/No	
plications : general laboratory use .	Yes/No	
rameter : PH . mV , Temp .	Yes/No	
range: -1 − 14 .	Yes/No	
mperature range: -5 - 105 C°.	Yes/No	
and temperature probe (plastic not glass).	Yes/No	
l and temperature probe (plastic not glass).	Ye	s/No



Accuracy: 2%.	Yes/No	
Temperature :manual by key or automatic recognized by probe (ATC)	Yes/No	
calibration: automatic one or two point for buffer (4,7,10)	Yes/No	
memory data and calibration memory Easy to read on a large screen	Yes/No	
You price Include startup set buffer Solution . (4,7,14)	Yes/No	
With Stand for probes , Dust cover , Water proof	Yes/No	
Complete system with all necessary solution for (calibration, cleaning ,storage) and probe with probe stand .	Yes/No	
Optional price : PH probe	Price	

Thermal Sealer machine

Brand name.

3 years warranty, 10 years availability spare parts .

Origin: USA, EURO

Simple.

Sealing band width: 250 mm . Over heat protection.

With cutting blade. Power: 700 w

Optional price:

220-240 V.

With cutting blade.

يجب تعبئة الجدول بالأسفل بالإضافة الى تقديم عرض الشركة التقني

Thermal Sealer machine	Compliance Yes / No
	(if no put your comments)
Manufacture	Manufacture



Model	Model
Origin	Origin
Delivery time	Delivery time
3 years warranty, 10 years availability spare parts.	Yes / No
Sealing band width : 250 mm .	Yes / No
Over heat protection .	Yes / No
With cutting blade .	Yes / No
Power: 700 w .	Yes / No
220- 240 V .	Yes / No
Optional price cutting blade ?	
Your warranty must be include all spare parts and labor .	Yes / No
Price should be include installation and team training in site .	Yes / No
Service & operation manuals are included & Date of manufacturing of system not less than 20 23.	Yes / No

